

HBO 2500 W/PIL

HBO-IC Microlithography lamps for ASML i-line systems | Microlithography lamps for ASML i-line systems




April 25, 2024, 01:42:07 HBO 2500 W/PIL

Technical data

Electrical data

Nominal voltage	28.0 V
Nominal current	90 A
Type of current	DC
Rated wattage	250000 W
Nominal wattage	250000 W

Dimensions & weight



Diameter	620 mm
Length	3400 mm
Length with base excl. base pins/connection	312.50 mm
Light center length (LCL)	149.0 mm ¹⁾
Electrode gap cold	7.0 mm

 $^{1)}$ Distance from end of base to tip of anode or cathode (cold)

Additional product data

Base anode (standard designation)	SFa30-6/50 ¹⁾
Base cathode (standard designation)	SFc30-6.5/50

 $^{1)}$ With cooling fins and cable connection (M 10) $\,$

Capabilities

Cooling	Forced ¹⁾
Burning position	Other ²⁾

^1) Maximum permissible base temperature: 200 $^{\circ}$ C

²⁾ Anode on top

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

Date of Declaration	05-03-2024		
Primary Article Identifier	4050300947396		
Candidate List Substance 1	Lead		
CAS No. of substance 1	7439-92-1		
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.		
Declaration No. in SCIP database	7eee76a5-c4d5-4b9f-b456-ddffe12f4ebb		

Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300947396	HBO 2500 W/PIL	Folding carton box 1	- x - x -		
4050300947402	HBO 2500 W/PIL	Folding carton box 1	- x - x -		
4050300634487	HBO 2500 W/PIL	Shipping carton box 1	320 mm x 230 mm x 605 mm	44.53 dm ³	6581.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.