

HBO 2001 W/NIL

HBO-IC Microlithography lamps for Nikon i-line systems | Microlithography lamps for Nikon i-line systems




Technical data

Electrical data

| | |
|-----------------|-----------|
| Nominal voltage | 260 V |
| Nominal current | 67 A |
| Type of current | DC |
| Rated wattage | 175000 W |
| Nominal wattage | 2000.00 W |

Dimensions & weight



| | |
|---|-------------------------|
| Diameter | 520 mm |
| Length | 2510 mm |
| Mounting length | 251.0 mm |
| Length with base excl. base pins/connection | 219.00 mm |
| Light center length (LCL) | 122.25 mm ¹⁾ |
| Electrode gap cold | 4.5 mm |

¹⁾ Distance from end of base to tip of anode or cathode (cold)

Additional product data

| | |
|----------------|---|
| Product remark | Also available as Super Longlife version with 2,250 h lifespan: HBO 2001 W/NIEL (4050300538211) |
|----------------|---|

Capabilities

| | |
|------------------|---------------------|
| Burning position | Other ¹⁾ |
|------------------|---------------------|

¹⁾ Anode underneath

Environmental information

| | |
|--|------------|
| Information according Art. 33 of EU Regulation (EC) 1907/2006 (RECh) | |
| Date of Declaration | 05-03-2024 |

Product datasheet

| | |
|----------------------------------|--|
| Primary Article Identifier | 4050300461489 |
| Candidate List Substance 1 | Lead |
| CAS No. of substance 1 | 7439-92-1 |
| Safe Use Instruction | The identification of the Candidate List substance is sufficient to allow safe use of the article. |
| Declaration No. in SCIP database | 51d17212-f48f-4e56-91b0-487db4ddc57b |

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|---------------------|---------------------------------|---|-----------------------|--------------|
| 4050300461489 | HBO 2001 W/NIL | Sliding sleeve 1 | 385 mm x 195 mm x 160 mm | 12.01 dm ³ | 1315.00 g |
| 4050300461496 | HBO 2001 W/NIL | Shipping carton box 6 | 510 mm x 420 mm x 420 mm | 89.96 dm ³ | 8804.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.