

ALLSEASON SUPER / ALLSEASON

Extra visibility under all weather conditions



Extra visibility

Due to yellow coating



Up to 30% more light

For better visibility and significantly shorter reaction times compared to standard halogen lamps



Better sight

Under all weather conditions



Better sight under all weather conditions

With up to 30% more light compared to standard lamps and an interference yellow coating ALLSEASON and ALLSEASON SUPER improve visibility while on the road under all weather conditions.

Product family datasheet

Technical data

Product description	Electrical Data				Photometric Data
	Power input	Nominal voltage	Nominal wattage	Test voltage	Nominal luminous flux
ALLSEASON SUPER / ALLSEASON H1	68 W ¹⁾	12 V	55 W	13.2 V	1550 lm
ALLSEASON SUPER / ALLSEASON H4	75 / 68 W ¹⁾	12 V	60/55 W	13.2 V	1650/1000 lm
ALLSEASON SUPER / ALLSEASON H7	58 W ¹⁾	12 V	55 W	13.2 V	1500 lm

Product description	Luminous flux tolerance	Physical Attributes & Dimensions	Lifetime Data		Certificates & standards	Environmental & Regulatory Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
		Diameter	Lifespan B3	Lifespan Tc	ECE category	Primary article identifier
ALLSEASON SUPER / ALLSEASON H1	±15 %	8.5 mm	150 hr	350 hr	H1	4050300504544 4008321168733
ALLSEASON SUPER / ALLSEASON H4	±15 / ±15 %	17.0 mm	150 / 150 hr ²⁾	350 / 350 hr ²⁾	H4	4050300435978 4052899503311 4008321168559
ALLSEASON SUPER / ALLSEASON H7	±10 %	12.0 mm	330 hr	550 hr	H7	4052899487239 4050300483153 4052899503335 4008321168757

Product description	Candidate list substance 1	Declaration no. in SCIP database
ALLSEASON SUPER / ALLSEASON H1	No declarable substances contained	No declarable substances contained
ALLSEASON SUPER / ALLSEASON H4	No declarable substances contained	No declarable substances contained
ALLSEASON SUPER / ALLSEASON H7	No declarable substances contained	No declarable substances contained

¹⁾ Maximum

²⁾ Filament 1

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Addon Technical Information Certificate overview OSRAM Argentina

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

