

TRUCKSTAR PRO

Brightest OSRAM truck light



Excellent brightness

More light allows to see farther and therefore react sooner



More than double the service life

Reduced downtime and fleet costs compared to standard lamps



Very high vibration resistance

Suitable for heavy duty applications

The most powerful halogen truck light from OSRAM

Discover TRUCKSTAR PRO signal lamps - the brightest truck light from OSRAM with excellent value for money. With up to 100% more light than standard lamps, extremely long life and very high vibration resistance these 24 volt lamps are ideal for professional drivers while reducing downtime and fleet costs. Thanks to the high vibration resistance, TRUCKSTAR PRO lamps are suitable even for heavy duty applications. Due to their impressive brightness and more than double the service life compared to standard lamps, the lamps improve your safety while driving on the road.



Product family datasheet

Technical data

Product description	Electrical Data					Photometric Data
	Power input	Nominal voltage	Nominal wattage	Power input tolerance	Test voltage	Nominal luminous flux
TRUCKSTAR PRO P21/5W	28 / 10 W	24 V	21/5 W	±6 / ±10 %	28.0 V	440/40 lm
TRUCKSTAR PRO W5W	7 W	24 V	5 W	±10 %	28.0 V	50 lm
TRUCKSTAR PRO P21W	28 W	24 V	21 W	±6 %	28.0 V	460 lm
TRUCKSTAR PRO PY21W	28 W	24 V	21 W	±6 %	28.0 V	250 lm
TRUCKSTAR PRO R10W	12.5 W	24 V	10 W	±10 %	28.0 V	125 lm
TRUCKSTAR PRO R5W	7 W	24 V	5 W	±10 %	28.0 V	50 lm
TRUCKSTAR PRO T4W	5 W	24 V	4 W	±10 %	28.0 V	35 lm

Product description	Luminous flux tolerance	Physical Attributes & Dimensions		
		Lamp base	Length	Diameter
TRUCKSTAR PRO P21/5W	±15 / ±20 %	BAY15d	52.5 mm	25.0 mm
TRUCKSTAR PRO W5W	±20 %	W2.1x9.5d	26.8 mm	10.0 mm
TRUCKSTAR PRO P21W	±15 %	BA15s	52.5 mm	25.0 mm
TRUCKSTAR PRO PY21W	±20 %	BAU15s	52.5 mm	25.0 mm
TRUCKSTAR PRO R10W	±20 %	BA15s	37.5 mm	16.0 mm
TRUCKSTAR PRO R5W	±20 %	BA15s	37.5 mm	16.0 mm
TRUCKSTAR PRO T4W	±20 %	BA9s	27.4 mm	9 mm

Product description	Diameter	Lifetime Data		Certificates & standards	Environmental & Regulatory Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
		Lifespan B3	Lifespan Tc	ECE category	Primary article identifier
TRUCKSTAR PRO P21/5W	25.0 mm	100 / 1000 hr	200 / 2000 hr	P21/5W	4008321798138 4062172158480 4052899423695 4062172121132
TRUCKSTAR PRO W5W	10.0 mm	1000 hr	4000 hr	W5W	4052899560543 4008321798077 4062172158305
TRUCKSTAR PRO P21W	25.0 mm	250 hr	500 hr	P21W	4008321852311 4062172285452 4052899341296 4062172285438 4062172158459

Product family datasheet

		Lifetime Data		Certificates & standards	Environmental & Regulatory Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
Product description	Diameter	Lifespan B3	Lifespan Tc	ECE category	Primary article identifier
TRUCKSTAR PRO PY21W	25.0 mm	250 hr	500 hr	PY21W	4052899341333 4062172121217 4062172121095 4062172121231 4062172158428 4008321856944
TRUCKSTAR PRO R10W	16.0 mm	1000 hr	2000 hr	R10W	4062172158398 4008321821232
TRUCKSTAR PRO R5W	16.0 mm	500 hr	1000 hr	R5W	4062172158367 4008321821201
TRUCKSTAR PRO T4W	9 mm	550 hr	1000 hr	T4W	4062172158336 4008321795106 4008321174055 4008321842589

Product description	Candidate list substance 1	Declaration no. in SCIP database
TRUCKSTAR PRO P21/5W	No declarable substances contained	No declarable substances contained
TRUCKSTAR PRO W5W	No declarable substances contained	No declarable substances contained
TRUCKSTAR PRO P21W	No declarable substances contained	No declarable substances contained
TRUCKSTAR PRO PY21W	No declarable substances contained	No declarable substances contained
TRUCKSTAR PRO R10W	No declarable substances contained	No declarable substances contained
TRUCKSTAR PRO R5W	No declarable substances contained	No declarable substances contained
TRUCKSTAR PRO T4W	No declarable substances contained	No declarable substances contained

Download Data

File	
	User instruction GPRS_Safety symbols instructions

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

