

X-RACER

Halogen headlight lamps for motorcycles



Areas of application

- Motorcycle headlight


Product family benefits

- Bluish white light for xenon look
- Optimum light for more time to react
- Up to 20 % more light (compared to standard halogen lamps)
- Bright and therefore pleasant light for the driver


Product family features

- Color temperature: up to 4,200 K
- Modern design with silver cap

Product family datasheet




Base




Base



Base



Base



Base

Product family datasheet

Technical data

Product description	Electrical data				Photometrical data	Dimensions & weight		Lifespan
	Power input	Nominal voltage	Nominal wattage	Test voltage	Luminous flux	Length	Diameter	Lifespan B3
64193XR	75 / 68 W ²⁾	12.0 V	60/55 W	13.2 V	1650/1000 lm	82.0 mm	17.0 mm	50 / 180 h ³⁾
64210XR	58 W ²⁾	12.0 V	55.00 W	13.2 V	1500 lm	59.0 mm	12.0 mm	100 h
64212XR ¹⁾	43 W ²⁾	12.0 V	35.00 W	13.2 V	800 lm	67.0 mm	10.0 mm	400 h
64327XR		12.0 V	35/35 W	13.2 V	650/465 lm	71.0 mm	14.7 mm	75 / 150 h
64211XR	62 W ²⁾	12.0 V	55.00 W	13.2 V	1350 lm	67.0 mm	12.0 mm	350 h
64185XR	36.8 / 36.8 W ²⁾	12.0 V	35/35 W	13.2 V	820/520 lm	82.0 mm	17.0 mm	75 / 150 h ³⁾

Product description	Lifespan Tc	Additional product data	Certificates & standards	Country specific categorizations
		Base (standard designation)	ECE category	Order reference
64193XR	100 / 380 h ³⁾	P43t	H4	64193XR
64210XR	200 h	PX26d	H7	64210XR
64212XR ¹⁾	800 h	PGJ19-1	H8	64212XR
64327XR	120 / 300 h	BA20d	S2	64327XR-01B 35/
64211XR	580 h	PGJ19-2	H11	64211XR
64185XR	150 / 300 h ³⁾	PX43t	HS1	64185XR

¹⁾ Lamp complies with ECE R 37 and SAE (DOT) regulations

²⁾ Maximum

³⁾ Filament 1

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.