

LEDFOG101

LEDDriving FOG | – LED fog lights



Areas of application

- Daytime running light
- Fog light
- Suitable for 12 V and 24 V on-board power supply systems

Product benefits

- 5 year guarantee
- Homogenous light, without light points
- Low energy consumption
- Lens resistant against gravel impact according to ASTM D256 and ISO 179
- Automatic operation thanks to intelligent control
- Easy installation

Product features

- LED fog light with daytime running light functionality
- Lightguide solution with high-quality LED technology
- Color temperature: up to 6,000 K
- Long lifetime: up to 5,000 h
- Certified according to ECE, SAE, CCC regulations
- OEM technology
- Type of protection: IP67

Product datasheet

Technical data

Electrical data

Nominal wattage	16.00 ... 24.00 W
-----------------	-------------------

Photometrical data

Color temperature	6000/5200 K
-------------------	-------------

Dimensions & weight

Product weight	1550.00 g
----------------	-----------

Certificates & standards

Approval marks – approval	E1 approval
---------------------------	-------------

Country specific categorizations

Order reference	LEDFOG101 BK 12
-----------------	-----------------

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321890566	LEDFOG101	Folding carton box 1	288 mm x 154 mm x 204 mm	9.05 dm ³	1816.00 g
4008321890573	LEDFOG101	Shipping carton box 4	634 mm x 306 mm x 231 mm	44.81 dm ³	8808.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

Guarantee terms are available at

▶ www.osram.com/am-guarantee

Legal advice

ECE E1 approval

ECE R19/R87 approval

Product pending homologation in Spain

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.
