

XENARC ULTRA LIFE D3S

Superior life and 10 year guarantee



10 year OSRAM guarantee

For a worry-free driving pleasure. Refer to www.osram.com/am-guarantee for precise conditions



Extra lifetime

Up to four times longer lifetime compared to standard xenon lamps



More durability

For longer replacement cycles and additional reliability and comfort



The durable light with up to four times longer lifetime

XENARC ULTRA LIFE xenon lamps were developed with durability in mind. These long-life headlight lamps make life just that little bit more hassle-free, thanks to a lifetime up to four times longer compared to standard xenon lamps. Besides, these reliable lights impress with a service life up to 300,000 km (with an average annual mileage of 14,259 km and 60% light on)! For XENARC ULTRA LIFE lamps, OSRAM provides a unique 10 year guarantee for end consumers (www.osram.com/am-guarantee). Thus, you not only save money on costly replacements, but also save yourself future stress and downtime. Please note: XENARC lamp change is recommended to be carried out by a professional.

Product datasheet

Technical data


Electrical Data

Power input	35 W
Nominal voltage	42.0 V
Nominal wattage	35 W
Test voltage	13.5 V
Power input tolerance	±3 %

Photometric Data

Nominal luminous flux	3200 lm
Luminous flux tolerance	±15 %
Color temperature	4300 K

Physical Attributes & Dimensions



Diameter	9 mm
Product weight	60.20 g
Length	83.2 mm
Lamp base	PK32d-5

Lifetime Data

Guarantee	10 years
-----------	----------

Capabilities

Technology	HID
------------	-----

Certificates & standards


ECE category	D3S ¹⁾
Approval marks – approval	E1 approval

Product datasheet

1) To be operated only with approved electronic control gear

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of declaration	29-10-2024
Primary article identifier	4052899425606 4062172404273 4052899429710
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	a4977431-0469-4938-bbae-2f7fbc300030 4dac5460-9f2d-4974-8f46-2378b4246f3e



ref_pim_ams_p_productinfographic

s



Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899425606	XENARC ULTRA LIFE D3S	Folding carton box 1	53 mm x 46 mm x 92 mm	0.23 dm ³	83.00 g
4052899425613	XENARC ULTRA LIFE D3S	Shipping carton box 4	115 mm x 101 mm x 103 mm	1.20 dm ³	346.00 g
4052899429710	XENARC ULTRA LIFE D3S	Hard Cover Box 2	113 mm x 48 mm x 106 mm	0.58 dm ³	212.00 g
4062172022088	XENARC ULTRA LIFE D3S	Shipping carton box 4	122 mm x 106 mm x 121 mm	1.56 dm ³	505.00 g
4062172404273	XENARC ULTRA LIFE D3S	HFB ECO 2	100 mm x 51 mm x 120 mm	0.61 dm ³	151.00 g
4062172404280	XENARC ULTRA LIFE D3S	Shipping carton box 4	113 mm x 111 mm x 134 mm	1.68 dm ³	345.00 g

Product datasheet

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File	
	Brochures ULTRA LIFE Leaflet EN
	ref_pim_amsproduct360degreeimages XENARC ULTRA LIFE D3S 66340ULT

Safety advice

XENARC lamp change is recommended to be carried out by a professional.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



OSRAM