OSRAM

LEDriving BASIC T4W



Product family datasheet

Technical data

9.5 mm

	Product information General Pro Information			Electrical Data		
Product description	Application (Category and Product specific)	Product type (off- road vs. on-road)	Global o		Power input	Nominal voltage
LEDriving BASIC ≙ T4W	Mainly used for signal/ indicator/interior applications	Off-road ≙ T4W	3750CW	/	0.78 W	12.0 V
			Photometric Data			Physical Attributes & Dimensions
Product description	Nominal wattage	Test voltage	Nominal I		Luminous flux	Diameter
					tolerance	
LEDriving BASIC	0 W	13.5 V	30 lm			9.5 mm
LEDriving BASIC ≜ T4W	0 W		1		tolerance	ntal & n rt. 33 of ion (EC)

Product description	Candidate list substance 1	CAS No. of substance	Safe use instruction	Declaration no. in SCIP database
LEDriving BASIC ≙ T4W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	9add2d47-cd43- 47d0-90e8- b42553d559f6 aadf4566-2f5c-420c- 940e-ab52c14c2128 dc70588f-5433- 4c78-9a81- 18450deb8f7c 4ed996ff-d5b8-4576- b168-a975922e67e5

2000 hr

2000 hr

LED

4052899463271 | 4052899414617 | 4052899463066 | 4052899414655

Product family datasheet

Download Data

File



User instruction

GPRS_Safety symbols instructions



Brochures

LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conformOnly approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.