

# LEDiving BASIC P21W



Product family datasheet

Technical data

Product description	Electrical Data					Photometric Data
	Power input	Nominal voltage	Nominal wattage	Power input tolerance	Test voltage	Nominal luminous flux
LEDDriving BASIC $\triangleq$ P21W	1.44 W	12 V	1 W	$\pm 20\%$	13.5 V	85 lm

Product description	Physical Attributes & Dimensions			
	Lamp base	Length	Diameter	Diameter
LEDDriving BASIC $\triangleq$ P21W	BA15s	38.2 mm	20.0 mm	20.0 mm

Product description	Lifetime Data		Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
	Lifespan B3	Lifespan Tc	Primary article identifier	Candidate list substance 1
LEDDriving BASIC $\triangleq$ P21W	2000 hr	2000 hr	4052899463318   4052899414471   4052899414457	Lead

Product description	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
LEDDriving BASIC $\triangleq$ P21W	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	d093b426-00c5-4f97-9516-27dd98167ef2   ccdfc44b-95fd-4b60-97d3-317a31be77c4   c583693a-46e5-4c4f-83a9-dac2ada6ba15

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conformOnly approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

