

# LEDDriving BASIC P21/5W



Product family datasheet

Technical data

Product description	Electrical Data					Photometric Data
	Power input	Nominal voltage	Nominal wattage	Power input tolerance	Test voltage	Nominal luminous flux
LEDriving BASIC $\triangleq$ P21/5W	1.44 W	12 V	1 W	$\pm 20\%$	13.5 V	85/25 lm

Product description	Physical Attributes & Dimensions			
	Lamp base	Length	Diameter	Diameter
LEDriving BASIC $\triangleq$ P21/5W	BAY15d	38.2 mm	20.0 mm	20.0 mm

Product description	Lifetime Data		Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
	Lifespan B3	Lifespan Tc	Primary article identifier	Candidate list substance 1
LEDriving BASIC $\triangleq$ P21/5W	2000 hr	2000 hr	4052899463295   4052899414518   4052899414495	Lead

Product description	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
LEDriving BASIC $\triangleq$ P21/5W	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	9bf3b981-7442-439c-a86d-e513fc794734   fe6d71fd-c80e-400d-8cc2-14ed29394294   1d480114-7d33-4144-80cc-0d5f7210d25e

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conformOnly approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

