OSRAM

LEDriving BASIC R5W



Product family datasheet

Technical data

	Electrical Data					Photom etric Data
Product description	Power input	Nominal voltage	Nominal wattage	Power input toleranc e	Test voltage	Nominal luminou s flux
LEDriving BASIC ≜ R5W	0.96 W	12 V	0 W	±20 %	13.5 V	55 lm

LEDRIVING BASIC = R5W	0.96 W 12 V		U W	±20 %	13.5 V	55 LM	
	Physical Attributes & Dimensions						
Product description	Lamp base	Length	Diamete	r	Diameter		
LEDriving BASIC	BA15s	29.0 mm	19.0 mm	ı	19.0 mm		
	Lifetime Data	Lifetime Data		Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Product description	Lifespan B3	Lifespan Tc	Primary article identifier	Candidat substanc			
LEDriving BASIC ≜ R5W	2000 hr	2000 hr	4052899463332 4052899414556 4052899463127 4052899414532	Lead			

Product description	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
LEDriving BASIC ≜ R5W	7439-92-1	The identification of	12c61241-8e84-
		the Candidate List substance is	49d2-aad6- 61ee9185fc4c
		sufficient to allow	a74edd59-fe84-466f-
		safe use of the	9e9c-d76036657cbc
		article.	4deab8c0-c089-
			4d6a-90f4-
			3738f5af799e
			e8c7bd92-d6cb-4cf2-
			9e8f-8360bae74918
			eb08c6c5-5573-
			4254-af17-
			5f6a4f492b5f

Product family datasheet

Download Data

File



User instruction

GPRS_Safety symbols instructions



Brochures

LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conformOnly approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

