

PrevaLED Bar G3

Area and Bar Light Engines



Product family features

- Module efficacy: up to 171 lm/W
- Average lifetime (L80 B10): 50,000 h (temperature at $T_c = 55\text{ °C}$)
- Available module length: 1 ft/280 mm or 2 ft/560mm
- Available with luminous flux: 1,156 lm, 2,312 lm and 3,572 lm
- Available with color temperature: 3,000 K, 4,000 K
- High initial color consistency: ≤ 3 SDCM
- CE marked

Product family benefits

- 3-row LED module suitable for 3 x 11 optics
- Cut out area for shadow-free wiring
- Push-in connector for automated wiring

Areas of application

- Retail
- Supermarkets
- Industry

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Sales and Technical Support

Sales and Technical Support www.osram.com

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.
