OSRAM

LEDriving SLT C5W 6421



LED replacement lamp with a color temperature of up to 5,800 K

Modern and intense uniform illumination



Replaces all conventional C5W 24V lamp bases

Easy upgrade to LED technology with plug & play solution



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for Festoon types

LEDriving SLT C5W replacement lamps offer a modern and intense light with a color temperature up to 5,800 Kelvin. These replacement lamps are suitable for all conventional C5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SLT lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

LEDriving SLT ≙C5W

	Product information		General Pro Information	duct	Electr	ical Data	
Product description	Application (Category and Product specific)	Product type (off- road vs. on-road)	Global order reference	-	Nomi	nal voltage	Nominal wattage
LEDriving SLT ≙C5W	Mainly used for signal/ indicator/interior applications	Off-road ≙ C5W	6421DWP		24 V		0 W
			Photometric Data				
Product description	Power input tolerance	Test voltage	Light color LED	Luminou flux tolerance		Color tempera	ture
LEDriving SLT ≙C5W	±30 %	28.0 V	Cool white	±30 %		5700 K	

	Physical Attributes	Physical Attributes & Dimensions					
Product description	Diameter	Diameter	Lamp base	Le	ngth		
LEDriving SLT ≙C5W	10.8 mm	10.8 mm	SV8.5-8 42		.0 mm		
		Lifetime Data		Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Product description	Product weight	Lifespan Guarantee	Lifespan	Technology	Primary article		

Tc

3.10 g

3000 hr

4 years

В3

1500 hr

LED

Product description	Candidate list substance 1	CAS No. of substance	Safe use instruction	Declaration no. in SCIP database
LEDriving SLT ≙C5W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	72d180f0-b282-4aac- aff9-81da2984cb96 10862d65-5c48- 46de-988d- a470bf9a9d88

identifier

4062172410779 |

4062172409780

Product family datasheet

Download Data

File



User instruction
GPRS_Safety symbols instructions

Safety advice

Application advice: For more detailed application information and graphics please see product datasheet and user manual.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

