


Lightbar FX500-CB SM

Higher luminosity guarantees improved safety on the road



Central and individual installation

Individual installation is possible thanks to twofold ECE certification



Lighting distance up to 440 meters

Improved far and near field illumination



Combo Beam

Combined beam of light



LED auxiliary lights enhance driving pleasure

Improved far field illumination on dark rural and dirt roads – it's no problem for the LEDriving Lightbar FX500-CB. Its 20 intense, high-performance LEDs give the LED high beam a light distance up to 440 meters and ensure improved road safety for drivers.

Even at dusk or in compromised lighting conditions, the LED bars for automobiles provide daylight conditions at a strong 6000 Kelvin without needlessly blinding oncoming traffic. The intelligent reflector design diverts the light from the LEDs so that oncoming traffic is only indirectly exposed to the light. The light is evenly distributed at a five degree angle.

Robust, durable and versatile

Whether used as a LED working light or as an auxiliary high beam for the car – the powerful performance and long life of

the LEDriving Lightbar FX500-CB make it a compelling choice. Equipped for a wide range of uses, it defies environmental factors and is particularly robust thanks to the quality craftsmanship of its materials and hard-wearing polycarbonate lens.

The integrated driver and thermal management system regulates the temperature of the LED automotive headlight and prevents damage caused by overheating. Full polarity protection ensures the LEDs are automatically shut off in the event of excess voltage.

Brightness for a wide range of uses

The LEDriving Lightbar FX500-CB is pure pleasure both on and off-road. The ECE-compliant LED auxiliary light ensures better visibility and thus improved safety on roads. In addition, it adds a smart touch that enhances the off-road style of the vehicle.

The LED headlight can be mounted on 12V vehicles as well as agricultural machines, utility vehicles, recreational, off-road and 4x4 vehicles. The power package with an intense 5500 lumen brightness scores with the highest optical efficiency and homogeneous light distribution with reduced glare.

Technical data

Product information

Application (Category and Product specific)	Additional high beam application
---	----------------------------------

General Product Information

Global order reference	LEDDL104-CB SM
------------------------	----------------


Electrical Data

Nominal voltage	12/24 V
Test voltage	13.5 V

Photometric Data

Nominal luminous flux	5500 lm
Color temperature	6000 K

Physical Attributes & Dimensions



Product weight	2100.00 g
----------------	-----------

Lifetime Data

Lifespan Tc	5000 hr
Guarantee	5 years

Additional product data

Connector to lamp	DT Connector
-------------------	--------------

Capabilities

Technology	LED
------------	-----

Certificates & standards

Approval marks – approval	E4 approval
Type of protection	IP67
Standards	ECE R10, R112

Logistical data

Commodity code	85122000900
----------------	-------------

Environmental & Regulatory Information





Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4052899614079
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	6da87b7d-5e14-42a4-b600-16a278fbfb38

Logistical Data









Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899614079	Lightbar FX500-CB SM	Folding carton box 1	638 mm x 137 mm x 90 mm	7.87 dm ³	2399.00 g
4052899614086	Lightbar FX500-CB SM	Shipping carton box 4	655 mm x 295 mm x 208 mm	40.19 dm ³	10238.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File	
	User instruction LEDriving
	User instruction GPRS_Safety symbols instructions
	Movie application LEDriving D and W Image Video Bringing light to life (EN)
	Movie application Working and Driving Lights Amarok Winter

Product datasheet

	Movie application LEDriving Driving and Working Lights Reference Video (EN)
	Movie application OSRAM LEDdriving and working lights Imagefilm (EN)
	Movie application LEDriving driving & working lights in application (EN)
	Movie application OSRAM Quality Testing LEDriving working and driving lights (EN)
	Video Light is Quality -OSRAM LEDriving Driving and Working Lights Quality Tests (EN)
	Video OSRAM LEDriving driving and working lights: The night doesn't stand a chance
	Video OSRAM LEDriving driving and working lights in action - From on road to off road applications (EN)
	Video Reference Number made easy - Making sure your LEDriving Driving Lights are legal on public roads

Legal advice

Single mounting – installation in pairs is not necessary, two certified light sourcesPrecise terms and conditions at:
www.osram.com/guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



OSRAM