## **OSRAM**

# Lightbar FX500-CB

Higher luminosity guarantees improved safety on the road





Combo Beam Combined beam of light



**Lighting distance up to 440 meters**Improved far and near field illumination



Beam angle 5°
Exceptionally focused beam angle



#### LED auxiliary lights enhance driving pleasure

Improved far field illumination on dark rural and dirt roads – it's no problem for the LEDriving Lightbar FX500-CB. Its 20 intense, high-performance LEDs give the LED high beam a light distance up to 440 meters and ensure improved road safety for drivers.

Even at dusk or in compromised lighting conditions, the LED bars for automobiles provide daylight conditions at a strong 6000 Kelvin without needlessly blinding oncoming traffic. The intelligent reflector design diverts the light from the LEDs so that oncoming traffic is only indirectly exposed to the light. The light is evenly distributed at a five degree angle.

#### Robust, durable and versatile

Whether used as a LED working light or as an auxiliary high beam for the car – the powerful performance and long life of the LEDriving Lightbar FX500-CB make it a compelling

#### Product family datasheet

choice. Equipped for a wide range of uses, it defies environmental factors and is particularly robust thanks to the quality craftsmanship of its materials and hard-wearing polycarbonate lens.

The integrated driver and thermal management system regulates the temperature of the LED automotive headlight and prevents damage caused by overheating. Full polarity protection ensures the LEDs are automatically shut off in the event of excess voltage.

#### Brightness for a wide range of uses

The LEDriving Lightbar FX500-CB is pure pleasure both on and off-road. The ECE-compliant LED auxiliary light ensures better visibility and thus improved safety on roads. In addition, it adds a smart touch that enhances the off-road style of the vehicle.

The LED headlight can be mounted on 12V vehicles as well as agricultural machines, utility vehicles, recreational, off-road and 4x4 vehicles. The power package with an intense 5500 lumen brightness scores with the highest optical efficiency and homogeneous light distribution with reduced glare.

## Product family datasheet

#### Technical data

|                     | Product information                         | General Produc            | ct       | Electrical Data                                                                                                    |                            | Photom<br>etric<br>Data      |
|---------------------|---------------------------------------------|---------------------------|----------|--------------------------------------------------------------------------------------------------------------------|----------------------------|------------------------------|
| Product description | Application (Category and Product specific) | Global order<br>reference |          | Nominal wattage                                                                                                    | e Test<br>voltage          | Nominal<br>luminou<br>s flux |
| Lightbar FX500-CB   | Additional high beam application            | LEDDL104-CB               |          | 68.00 W                                                                                                            | 13.5 V                     | 5500 lm                      |
|                     | Lifetime Data                               | Capabilities              | Certific | ates & standards                                                                                                   |                            |                              |
| Product description | Lifespan Tc                                 | Technology                | Approva  | •                                                                                                                  | ype of protection          |                              |
| Lightbar FX500-CB   | 5000 hr                                     | LED                       | Е4 аррі  | oval IP                                                                                                            | 67                         |                              |
|                     |                                             | Logistical data           |          | Environmental & Regulatory Information<br>Information according Art. 33 of EU<br>Regulation (EC) 1907/2006 (REACh) |                            |                              |
|                     |                                             |                           |          | , ,                                                                                                                |                            |                              |
| Product description | Standards                                   | Commodity cod             | de       | Primary article identifier                                                                                         | Candidate l<br>substance 1 |                              |

| Product description | CAS No. of substance | Safe use instruction                                                                               | Declaration no. in<br>SCIP database          |
|---------------------|----------------------|----------------------------------------------------------------------------------------------------|----------------------------------------------|
| Lightbar FX500-CB   | 7439-92-1            | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 3fb4e8db-b861-<br>4743-a139-<br>730e69bb83fc |

### Product family datasheet

#### Download Data

|         | File                                                                                                       |
|---------|------------------------------------------------------------------------------------------------------------|
| <b></b> | User instruction GPRS_Safety symbols instructions                                                          |
| Z       | User instruction<br>LEDriving                                                                              |
| D       | Movie application<br>LEDriving D and W Image Video Bringing light to life (EN)                             |
| D       | Movie application<br>Working and Driving Lights Amarok Winter                                              |
| D       | Movie application<br>LEDriving Driving and Working Lights Reference Video (EN)                             |
| D       | Movie application OSRAM LEDdriving and working lights Imagefilm (EN)                                       |
| D       | Movie application LEDriving driving & working lights in application (EN)                                   |
| D       | Movie application OSRAM Quality Testing LEDriving working and driving lights (EN)                          |
| D       | Video<br>Light is Quality -OSRAM LEDriving Driving and Working Lights Quality Tests (EN)                   |
| D       | Video<br>OSRAM LEDriving driving and working lights: The night doesn't stand a chance                      |
| D       | Video<br>OSRAM LEDriving driving and working lights in action - From on road to off road applications (EN) |
| D       | Video<br>Reference Number made easy - Making sure your LEDriving Driving Lights are legal on public roads  |

#### Legal advice

In vehicles with 12/24 volts, auxiliary lights must be installed in pairsPrecise terms and conditions at: www.osram.com/guarantee

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.















