

LEDDriving SL P21W YELLOW

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications

Available in Amber



Replaces conventional P21W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for P21W

LEDDriving SL P21W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional P21W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| Product description | Product information | | General Product Information | Electrical Data | |
|-----------------------------|-------------------------------------|--|-----------------------------|-----------------|-----------------|
| | Product type (off-road vs. on-road) | Application (Category and Product specific) | Global order reference | Power input | Nominal voltage |
| LEDriving SL $\hat{=}$ P21W | Off-road $\hat{=}$ P21W | Mainly used for signal/ indicator applications | 7506DYP | 1.8 W | 12.0 V |

| Product description | Nominal wattage | Test voltage | Photometric Data | | Physical Attributes & Dimensions |
|-----------------------------|-----------------|--------------|-----------------------|-------------------------|----------------------------------|
| | | | Nominal luminous flux | Luminous flux tolerance | Diameter |
| LEDriving SL $\hat{=}$ P21W | 1 W | 13.5 V | 50 lm | \pm 25 % | 25.0 mm |

| Product description | Lifetime Data | | Capabilities | Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | |
|-----------------------------|---------------|-------------|-------------------|---|----------------------------|
| | Lifespan B3 | Lifespan Tc | Technology | Primary article identifier | Candidate list substance 1 |
| LEDriving SL $\hat{=}$ P21W | 1500 hr | 4000 hr | LED ¹⁾ | 4062172152228 4062172401357 | Lead |

| Product description | CAS No. of substance 1 | Safe use instruction | Declaration no. in SCIP database |
|-----------------------------|------------------------|--|--------------------------------------|
| LEDriving SL $\hat{=}$ P21W | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 558ba419-9f08-4a0e-b0ad-fa29ec684e7c |

¹⁾ Light-emitting diode lamp

Product family datasheet

Download Data

| File | |
|---|---|
|  | Brochures LEDriving Retrofits - Exchange overview (EN) |

Safety advice

Canbus compatible Coloured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.