

# LEDDriving SL P27/7W RED

Ideal replacement for any vehicle



**Suitable for various vehicle exterior applications**

Available in Red



**Replaces conventional P27/7W lamps**

Easy upgrade to LED technology with plug & play solutions



**Reliable OSRAM quality stands for less lamp replacements**

4-year OSRAM guarantee (refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee) for precise conditions)



### Suitable LED replacement for P27/7W

LEDDriving SL P27/7W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional P27/7W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

# Product datasheet

## Technical data

### Product information

Product type (off-road vs. on-road)	Off-road $\triangleq$ P27/7W
Application (Category and Product specific)	Mainly used for signal/ indicator applications

### General Product Information

Global order reference	3157DRP
------------------------	---------


### Electrical Data

Power input	1.8 W
Nominal voltage	12.0 V
Nominal wattage	1 W
Test voltage	13.5 V
Power input tolerance	$\pm 25$ %

### Photometric Data

Nominal luminous flux	60/10 lm
Luminous flux tolerance	$\pm 25$ %
Light color LED	Red

### Physical Attributes & Dimensions



Diameter	25.7 mm
Product weight	13.30 g
Length	49.0 mm
Lamp base	W2.5x16q

### Lifetime Data

Lifespan B3	1500 hr
-------------	---------

## Product datasheet

Lifespan Tc	4000 hr
Guarantee	4 years

### Capabilities

Technology	LED <sup>1)</sup>
------------	-------------------

<sup>1)</sup> Light-emitting diode lamp

### Environmental & Regulatory Information



Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4062172151689   4062172401777
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	a5c512b0-7fa2-4907-bc1f-816fe7f2d8ed

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172151689	LEDDriving SL $\triangleq$ P27/7W	Blister 2	135 mm x 95 mm x 18 mm	0.35 dm <sup>3</sup>	39.00 g
4062172151696	LEDDriving SL $\triangleq$ P27/7W	Shipping carton box 10	119 mm x 109 mm x 151 mm	1.96 dm <sup>3</sup>	228.00 g
4062172401777	LEDDriving SL $\triangleq$ P27/7W	BLI ECO 2	95 mm x 27 mm x 135 mm	0.35 dm <sup>3</sup>	39.00 g
4062172401784	LEDDriving SL $\triangleq$ P27/7W	Shipping carton box 10	142 mm x 104 mm x 104 mm	1.54 dm <sup>3</sup>	227.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Download Data

File
 User instruction GPRS_Safety symbols instructions
 Brochures LEDDriving Retrofits - Exchange overview (EN)

### Safety advice

## Product datasheet

Canbus compatible Coloured lamps for usage behind coloured glass

### Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

### Application advice

For more detailed application information and graphics please see product datasheet.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

The OSRAM logo is displayed in a bold, orange, sans-serif font.