Product family datasheet

LEDriving SL P21/5W WHITE

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications Available in Cool White



Replaces conventional P21/5W lamps Easy upgrade to LED technology with

plug & play solutions



Reliable OSRAM quality stands for less lamp replacements 4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for P21/5W

LEDriving SL P21/5W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional P21/5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

LEDriving SL \doteq P21/5W

	Electrical Data							Photom etric Data
Product description	Power input	Nominal vo	ltage	Nominal watt	age	Power input toleranc e	Test voltage	Nominal luminou s flux
LEDriving SL ≙ P21/5W	2.50 / 0.5 W	12 V		1 W		±25 %	13.5 V	145/30 lm
	Physical Attributes & Dimensions							
Product description	Lamp base	e	Length	I	Diameter		Diameter	
LEDriving SL \triangleq P21/5W	BAY15d		52.5 mm	-	27.0 mm		27.0 mm	
	Lifetime Data			Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)				
Product description	Lifespan B3 Life Tc		Lifespan Tc	Primary article identifier		Candidate list substance 1		

Product description	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
LEDriving SL ≙ P21/5W	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	026eb835-3aa5- 4bfa-a635- bb4b42c468ab

4000 hr

4062172151726 |

4062172401197

Lead

1500 hr

_

Product family datasheet

Download Data

File
User instruction GPRS_Safety symbols instructions
Brochures LEDriving Retrofits - Exchange overview (EN)

Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.