OSRAM

LEDinspect TWIST250

Inspectionlights





Multi-Angle Flex & Twist

High flexibility and diverse adjustment possibilities thanks to multi angle positioning



250 Lumen

2 light functions:Up to 250lm -highUp to 125lm -low



2in1

Inspectionlight & Torchlight function



2-year-OSRAM guarantee*

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.



Light is versatile

With the TWIST 250 you have the possibility to easily control the direction of the light beam. A light output of up to 250 lumens and a colour temperature of up to 6000K, make the TWIST 250 ideal for use in workshops and beyond. Lightweight, robust and with a 360° rotation and a 180° grid function, it is an optimal tool for targeted lighting. Mains charger included. In addition, OSRAM provides a 2-year guarantee on this product*

Technical data

Product information

Order reference	LEDIL412
Application (Category and Product specific)	LED inspection lights

Electrical data

Nominal wattage	814 W
Nominal voltage	37 V


Photometrical data

Color temperature	6000 К
Luminous flux	250 lm
Light color LED	White

LED module information

Number of LEDs per module	2

Dimensions & weight







Product weight	48800 g
Length	2430 mm
Width	500 mm
Height	440 mm

Colors & materials

Base color	Black / Orange
------------	----------------

Lifespan

Guarantee	2 years

Additional product data

Type of Battery	Rechargeable
Number of included batteries	1
Scope of battery	Yes
Battery	High-quality lithium-ion battery

Capabilities

Technology	LED

Certificates & standards

Standards	CE/EMC/MSDS/ROHS
IK Class	IK09

Country specific categorizations

Order reference	LEDIL412

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Date of Declaration	07-03-2024
Primary Article Identifier	4052899623934
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	c20eb463-09bd-4c1e-8bd5-69238c3db62e







Detail Detail Detail





Detail Detail

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899623934	INSPECTION LAMP	Folding carton box 1	87 mm x 55 mm x 362 mm	1.73 dm³	572.00 g
4052899624054	INSPECTION LAMP	Shipping carton box	412 mm x 285 mm x 140 mm	16.44 dm³	3802.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

	File
太	User instruction LEDinspect TWIST 250
D	Movie application LEDinspect Inspection Lights Trailer

Application advice:

For more detailed application information and graphics please see product datasheet and user instruction.

*for precise conditions please refer to:

www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

