

# LEDinspect SLIM MAX1000

## Inspectionlights



### Dimmer Switch

Individually adjustable brightness levels with up to 1000 lm



### 1000 Lumen

Bright, white LED light and uniform light distribution



### Multi-Angle Light Output

High flexibility due to individual adjustment of the light beam



### 2-year-OSRAM guarantee\*

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.

## Product datasheet



### Light is versatile

This high-quality inspection light is perfect for professional and private use. With an integrated dimmer, you can select the appropriate brightness level with up to 1000lm for the task at hand with the SLIM MAX 1000. The ultra slim design combined with multi-angle positioning gives maximum flexibility and adjustability to give light exactly where needed. The SLIM MAX 1000 is rechargeable and cordless with Li-ion battery and can therefore provide constant light output. The lamp has an operating time of up to 1.5h with high light output or up to 10,5h with low light output. Charging cable and mains adaptor are included in the scope of supply. In accordance with the IP protection class IP65, this inspection light has protection against the ingress of dust and water and is tested for impact resistance in accordance with IK06. This inspection light has an integrated hook and magnets for hands-free work, making it ideal as a light for manual tasks, car repairs and for everyday use. In addition, OSRAM grants a 2-year guarantee on this product\*

Technical data

Product information

|                                             |                       |
|---------------------------------------------|-----------------------|
| Order reference                             | LEDIL410              |
| Application (Category and Product specific) | LED inspection lights |

Electrical data

|                 |         |
|-----------------|---------|
| Nominal wattage | 10.00 W |
| Nominal voltage | 3.7 V   |


Photometrical data

|                   |         |
|-------------------|---------|
| Color temperature | 6000 K  |
| Luminous flux     | 1000 lm |
| Light color LED   | White   |

LED module information

|                           |   |
|---------------------------|---|
| Number of LEDs per module | 2 |
|---------------------------|---|

Dimensions & weight



|                |          |
|----------------|----------|
| Product weight | 340.00 g |
| Length         | 365.0 mm |
| Width          | 65.0 mm  |
| Height         | 50.0 mm  |

Colors & materials

|            |                |
|------------|----------------|
| Base color | Black / Orange |
|------------|----------------|

Lifespan

|           |         |
|-----------|---------|
| Guarantee | 2 years |
|-----------|---------|

Additional product data

|                              |                                  |
|------------------------------|----------------------------------|
| Type of Battery              | Rechargeable                     |
| Number of included batteries | 1                                |
| Scope of battery             | Yes                              |
| Battery                      | High-quality lithium-ion battery |

Capabilities

|            |     |
|------------|-----|
| Technology | LED |
|------------|-----|

Certificates & standards

|           |                  |
|-----------|------------------|
| Standards | CE/EMC/MSDS/ROHS |
| IK Class  | IK06             |

Country specific categorizations

|                 |          |
|-----------------|----------|
| Order reference | LEDIL410 |
|-----------------|----------|

Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |                                                                                                    |
|-----------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|
| Date of Declaration                                                   | 08-03-2024                                                                                         |
| Primary Article Identifier                                            | 4062172355674                                                                                      |
| Candidate List Substance 1                                            | Lead                                                                                               |
| CAS No. of substance 1                                                | 7439-92-1                                                                                          |
| Safe Use Instruction                                                  | The identification of the Candidate List substance is sufficient to allow safe use of the article. |
| Declaration No. in SCIP database                                      | 99d5749d-0f33-4ebf-9ff7-b17da405d236                                                               |



Detail



Detail

Product datasheet

Logistical Data

| Product code  | Product description | Packaging unit<br>(Pieces/Unit) | Dimensions (length<br>x width x height) | Volume               | Gross weight |
|---------------|---------------------|---------------------------------|-----------------------------------------|----------------------|--------------|
| 4062172355674 | INSPECTION LAMP     | Folding carton box<br>1         | 72 mm x 60 mm x<br>370 mm               | 1.60 dm <sup>3</sup> | 409.00 g     |
| 4062172355681 | INSPECTION LAMP     | Shipping carton box<br>6        | 390 mm x 165 mm x<br>150 mm             | 9.65 dm <sup>3</sup> | 2678.00 g    |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Application advice:

For more detailed application information and graphics please see product datasheet and user instruction.

\*for precise conditions please refer to:

[www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

