

LEDguardian ROAD FLARE



2 in 1

Can be used as a warning light and as a torch




360 degree rotation

The 360-degree rotating orange warning light function is visible from a great distance



Magnetic mounting


Thanks to the magnet function and the hook, the LED warning light can be attached in various ways.



3x AAA batteries included

Operational readiness. With the three AAA batteries supplied, the warning light is ready for use immediately after purchase

Product datasheet



Light is safety-See and be seen with OSRAM

Be prepared with OSRAM warning and safety lights. The LEDguardian ROAD FLARE is a compact LED warning light for various situations on the road and for minor inspection work on your vehicle. The 360 degrees rotating, orange, warning light function of the LEDguardian ROAD FLARE is visible from a great distance and can provide crucial information about a dangerous situation in an emergency. A total of 16 high-quality long-life LEDs offer three different operating modes: 360 ° rotating orange warning light function, permanent orange light function and a white torch function. In addition, the LEDguardian ROAD FLARE impresses with its non-slip, dirt-repellent surface, a practical hook for attachment and is so robust and resistant that it can even be run over by a car** without losing performance. The LEDguardian ROAD FLARE has been tested and validated in our certified environmental simulation laboratory for extreme external influences in terms of water, dust and impact from falls. According to the IP54 & IK07 protection classes, the LEDguardian ROAD FLARE is resistant to water, dust and impacts. With the three AAA batteries supplied, the warning light is ready for use immediately after purchase. OSRAM provides a 2-year guarantee on this product* The LEDguardian ROAD FLARE is not approved as a warning light in Germany in the sense of the German Road Traffic Licensing Regulations (StVZO). Please observe any special requirements and laws in countries outside Germany regarding the use and operation of an additional warning light in road traffic.*For precise conditions please refer to: www.osram.com/am-guarantee **Tested at a mid-range car at walking pace

Product datasheet

Technical data

Product information

Application (Category and Product specific)	Warning and safety lights
---	---------------------------

General Product Information

Global order reference	LEDSL303
------------------------	----------

Electrical Data

Nominal wattage	1 W
Nominal voltage	4.5 V

Photometric Data

Color temperature	6500 K
Nominal luminous flux	75 lm
Light color LED	Flash: orange/amber / Torch: white

Physical Attributes & Dimensions

Product weight	176.00 g
Length	111.0 mm
Width	101.0 mm
Height	111.0 mm

Colors & materials

Base color	Black
------------	-------

Lifetime Data

Guarantee	2 years
-----------	---------

Additional product data

Type of Battery	Alkaline
Scope of battery	Yes
Battery	3xAAA (Battery Lifetime 8h-20h)

Capabilities

Technology	LED
------------	-----

Certificates & standards

Type of protection	IP54
--------------------	------

Product datasheet

IK Class	IK07
-----------------	------

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of declaration	26-06-2024
Declaration no. in SCIP database	In work

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172295659	LEDguardian ROAD FLARE		- x - x -	14.57 dm ³	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Legal advice

* for precise conditions please refer to: www.osram.com/am-guarantee**Tested at a mid-range car at walking pace

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM