

# XENARC NIGHT BREAKER LASER (NEXT GEN) D3S

Brightest OSRAM xenon light



Up to 220% more brightness<sup>1)</sup>, 2)

More light allows to see farther and therefore react sooner compared to the minimum legal standard



Up to 250 m long beam

For better visibility



Up to 20% whiter light<sup>1)</sup>

More modern look compared to the minimum legal standard



For more customer satisfaction

3 year guarantee, refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee) for precise conditions



## The most powerful xenon light from OSRAM

XENARC NIGHT BREAKER LASER is the brightest OSRAM xenon light. This powerful lamp with efficient xenon technology ensures a better visibility on the road: up to 220% more brightness compared to the minimum legal standard. More light allows to see further and therefore react sooner. Added to this is the up to 250 meter long beam and up to 20% whiter light for more modern look (compared to the minimum legal standard). Discover the pure performance of XENARC NIGHT BREAKER LASER - the most powerful xenon light from OSRAM, available in D1S, D2S, D3S and D4S. Please note: XENARC lamp change is recommended to be carried out by a professional and in pairs.<sup>1)</sup> Compared to minimum ECE R98/R99 requirements<sup>2)</sup> D3S, D4S

Technical data

Product information

Product legal advice 1	1) Compared to minimum ECE R98/R99 requirements
Product legal advice 2	2) D3S, D4S

Electrical Data

Power input	35 W
Nominal voltage	42.0 V
Nominal wattage	35 W
Power input tolerance	±3 %
Test voltage	13.5 V

Photometric Data

Nominal luminous flux	3200 lm
Luminous flux tolerance	±15 %

Physical Attributes & Dimensions

Lamp base	PK32d-5
Length	83.2 mm
Diameter	9 mm
Product weight	60.20 g

Lifetime Data

Lifespan B3	2000 hr
Lifespan Tc	3000 hr

Capabilities

Technology	HID <sup>1)</sup>
------------	-------------------

<sup>1)</sup> High-intensity discharge lamp

Certificates & standards

ECE category	D3S <sup>1)</sup>
Approval marks – approval	E1 approval

<sup>1)</sup> To be operated only with approved electronic control gear

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of declaration	09-07-2024

Product datasheet


Primary article identifier	4052899631304   4052899631342
Declaration no. in SCIP database	In work

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172313636	XENARC NIGHT BREAKER LASER D3S		- x - x -	1.56 dm <sup>3</sup>	
4062172313728	XENARC NIGHT BREAKER LASER D3S		- x - x -	1.20 dm <sup>3</sup>	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File	
	Movie application Installation Video Xenarc Night Breaker Laser Opel Zafira (EN)

Safety advice

XENARC lamps should be replaced by a qualified mechanic.This product must only be operated with approved electronic control gear.

Legal advice

Light output compared to the minimum ECE R98/99 requirementsThis product must only be operated with approved electronic control gearXENARC lamps should be replaced by a qualified mechanicReduced UV emission | For projection headlights | ECE approval and DOT label± 450 lm

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

