Connection Cable 300 DT AX



3-meter cable length With a length of 3m, the cable is able to install appropriate lighting even on large vehicles



Easy Installation Specially designed to connect the LEDriving driving and working lights of the PX-, SX- and FX-Series to a power source



Matrix Portfolio A vehicle-specific lighting set-up can be put together individually. Mix & match. Vary and combine



OSRAM

2-year OSRAM Guarantee OSRAM products are innovative and technologically high-quality products that are carefully tested and subject to the strict monitoring undertaken by the OSRAM quality assurance system

Professional light for professional work



With the OSRAM LEDriving Professional Series PX working lights portfolio, it is now possible to find exactly the right lighting for a wide range of special professional tasks and applications. Additionally, they can be mounted in three different ways: Direct mounting, flexible standard mounting, and heavy-duty mounting. OSRAM has developed specially designed mounting kits and a cable with DT-connector. The LEDriving Connection Cable 300 DT AX is compatible with all OSRAM LEDriving working lights of the Professional Series PX and with the LEDriving driving and working lights of the SXand FX- series. It is suitable for 12V and 24V vehicles and with the DT connector it can provide a quick and easy connection to a power source for setup of the LEDriving driving and working lights. The conductor material is made of pure copper and with a length of 3m the cable is able to install appropriate lighting even on large vehicles. OSRAM provides a 2-year guarantee on this product1)2)1) Additional working lights without ECE approval for use as work lights are approved for use on any vehicle according to German Road Traffic Licensing Regulations (StVZO) §52 (7). However, they must not be used and switched on while driving. In addition, individual special regulations, and laws of countries outside Germany must be observed.2) For precise conditions refer to: www.osram.com/am-guarantee

Technical data

Product information

Order reference LEDPWL ACC 103			
Application (Category and Product specific)	Working & Driving Light Application		
Electrical data			
Nominal voltage	12/24 V		

Dimensions & weight





Product weight	249.00 g	
Length	3000 mm	
Lifespan		
Guarantee	2 years	
Additional product data		
Connector to lamp	DT Connector	
Certificates & standards		
Standards	ROHS/REACH	
Country specific categorizations		
Order reference	LEDPWL ACC 103	
Logistical data		

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

Date of Declaration	23-02-2024
Primary Article Identifier	4062172294805
Declaration No. in SCIP database	In work

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172294805	Connection Cable 300 DT AX LEDPWL ACC 103	Folding carton box 1	98 mm x 66 mm x 227 mm	1.47 dm³	302.00 g
4062172294812	Connection Cable 300 DT AX LEDPWL ACC 103	Shipping carton box 30	350 mm x 315 mm x 474 mm	52.26 dm ³	9850.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

	File
7	User instruction LEDriving PROFESSIONAL WORKING LIGHTS
D	Movie application OSRAM Quality Testing LEDriving working and driving lights (EN)
D	Movie application OSRAM LEDdriving and working lights Imagefilm (EN)
D	Movie application LEDriving Driving and Working Lights Reference Video (EN)

Safety advice

For detailed application information, please refer to the product data sheet and the user instruction

Legal advice

1) Additional working lights without ECE approval for use as work lights are approved for use on any vehicle according to German Road Traffic Licensing Regulations (StVZO) §52 (7). However, they must not be used and switched on while driving. In addition, individual special regulations, and laws of countries outside Germany must be observed.

2)For precise conditions refer to: www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

