Product family datasheet

OSRAM

TYREinflate 4000

TYREinflate 4000 OTIR4000



Inflation Time Inflate the tyre to the desired pressure in approximately 3,5 minutes ¹⁾²⁾



Deflator Valve For deflating too much air



Digital Auto Stop Automatic stop function when the preset pressure is reached



Cordless and rechargeable Can be used with or without direct power supply

Rechargable Digital Tyre Inflator



The OSRAM TYREinflate 4000 is a cordless and rechargeable tyre inflator with Li-Ion battery, making it an ideal companion for camping and road trips. The OTIR 4000 digital tyre inflator can inflate a tyre in just 3,5 minutes¹⁾²⁾. The auto stop function and the deflator valve help to keep the tyres optimally inflated. The backlit LED display and integrated LED light provide improved readability of the pressure settings and improved illumination of the working area even in reduced visibility conditions or at night. Memory setting means you can store pressures for up to 4 vehicles.

OSRAM offers a 2-year guarantee¹⁾ on this product.

1) For precise conditions please refer to: www.osram.com/am-guarantee

2) Based on inflating a 13" tyre from flat to 2.4 BAR

3) Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyres

Product family datasheet

Technical data

	Product information	ı		
Product description	Deflation valve	LED Light	Preset Function	Auto stop
TYRE inflate 4000	Yes	Yes	Yes	Yes
		Additional product dat	a	Capabilities
Product description	Storage Case	Display Type	Extras	Fuse
TYRE inflate 4000	Yes	Digital	Air hose, USB C charging cable,12 V D.C cable, 3 inflator adaptors, storage case	15 A
			ease	
		egulatory Information ng Art. 33 of EU Regulation)
Product description) Declaration no. in SCIP database

Product family datasheet

Download Data

	File
7	User instruction TYREinflate 4000
D	Movie application TYREinflate 4000 Product Video (EN)

Legal advice ¹⁾ For precise conditions please refer to: www.osram.com/am-guarantee

 $^{\rm 2)}$ Based on inflating a 13" tyre from flat to 2.41 BAR

³⁾ Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyresApplication advice:For more detailed application information and graphics please see product datasheet and the user instruction.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.