

XENARC NIGHT BREAKER 220 D1S



**Up to 220% more brightness¹⁾¹⁾
Compared to minimum ECE R98R99.
requirements.**

More light allows to see farther and therefore react sooner compared to the minimum legal standard



Up to 250 m long beam

For better visibility



**Up to 20% whiter light¹⁾¹⁾ Compared to
minimum ECE R98R99 requirements.**

More modern look compared to the minimum legal standard



The most powerful xenon light from OSRAM

XENARC NIGHT BREAKER 220 is the brightest OSRAM xenon light. This powerful lamp with efficient xenon technology ensures a better visibility on the road: up to 220% more brightness compared to the minimum legal standard. More light allows to see further and therefore react sooner. Added to this is the up to 250 meter long beam and up to 20% whiter light for more modern look (compared to the minimum legal standard). Discover the pure performance of XENARC NIGHT BREAKER 220 - the most powerful xenon light from OSRAM, available in D1S, D2S, D3S and D4S. Please note: XENARC lamp change is recommended to be carried out by a professional and in pairs.

Product datasheet

Technical data

Electrical Data

Power input	35 W
Nominal voltage	85.0 V
Nominal wattage	35 W
Test voltage	13.5 V
Power input tolerance	±3 %

Photometric Data

Nominal luminous flux	3200 lm
Luminous flux tolerance	±15 %

Physical Attributes & Dimensions

Diameter	9 mm
Product weight	60.70 g
Length	77.3 mm
Lamp base	PK32d-2

Lifetime Data

Lifespan B3	1500 hr
Lifespan Tc	3000 hr

Capabilities

Technology	HID ¹⁾
------------	-------------------

¹⁾ High-intensity discharge lamp

Certificates & standards

ECE category	D1S ¹⁾
--------------	-------------------

¹⁾ To be operated only with approved electronic control gear

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of declaration	05-08-2024
Primary article identifier	4062172398619 4062172397735
Declaration no. in SCIP database	In work


Logistical Data

Product datasheet

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172397735	XENARC NIGHT BREAKER 220 D1S		- x - x -	0.61 dm ³	
4062172397742	XENARC NIGHT BREAKER 220 D1S	Shipping carton box 4	- x - x -	1.68 dm ³	
4062172398619	XENARC NIGHT BREAKER 220 D1S		- x - x -	0.23 dm ³	
4062172398626	XENARC NIGHT BREAKER 220 D1S	Shipping carton box 4	- x - x -	1.20 dm ³	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File
 ref_pim_amsproduct360degreeimages XENARC ORIGINAL D1S 66140

Safety advice

XENARC lamps should be replaced by a qualified mechanic. This product must only be operated with approved electronic control gear.

Legal advice

Light output compared to the minimum ECE R112/R37 requirements. This product must only be operated with approved electronic control gear. XENARC lamps should be replaced by a qualified mechanic. Reduced UV emission | For projection headlights | ECE approval and DOT label ± 450 lm

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM