

# Wire Harness AX 1LS



## Connection of one light source

Wire harness suitable for the installation of one light source with one lighting function of the OSRAM LEDriving driving and working lights for 12 V vehicles



## OnOff switch integrated

For installation in the vehicles cabin to switch the OSRAM LEDriving working lights on or off as required



## Easy Installation

For easy installation of OSRAM LEDriving driving and working lights



## Bringing light to life with OSRAM LEDriving driving and working lights

To support the installation of the OSRAM LEDriving driving & working lights, OSRAM has developed a special series with suitable accessories for them. With the OSRAM Wire Harness AX 1LS, the OSRAM LEDriving driving & working lights, can now be installed quickly and easily on the appropriate vehicle. The OSRAM Wire Harness AX 1LS is a wire harness that is suitable for the installation of one light source with one lighting function. It also has an integrated on/off switch that can be installed in the vehicles cabin to switch the OSRAM LEDriving working lights on or off as required. The switch is only to be used for the OSRAM LEDriving working lights. The OSRAM Wire Harness AX 1LS is suitable for 12 V vehicles. OSRAM also offers a 2-year guarantee<sup>1)</sup>.

Product datasheet

Technical data


Product information

Order reference	LEDDL ACC 101
-----------------	---------------

Electrical data

Nominal voltage	12.0 V
-----------------	--------

Dimensions & weight



Product weight	275.00 g
Length	0.0 mm

Lifespan

Guarantee	2 years
-----------	---------

Country specific categorizations

Order reference	LEDDL ACC 101
-----------------	---------------

Logistical data

Commodity code	85444290900
----------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	16-05-2024
Primary Article Identifier	4062172147682
Declaration No. in SCIP database	In work




Logistical Data

Product datasheet

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172147682	Wire Harness AX 1LS	Folding carton box 1	175 mm x 82 mm x 177 mm	2.52 dm <sup>3</sup>	325.00 g
4062172147699	Wire Harness AX 1LS	Shipping carton box 8	362 mm x 335 mm x 190 mm	23.04 dm <sup>3</sup>	3045.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File	
	Movie application OSRAM Quality Testing LEDriving working and driving lights (EN)
	Movie application OSRAM LEDdriving and working lights Imagefilm (EN)
	Movie application LEDriving Driving and Working Lights Reference Video (EN)

Legal advice:

1) Precise terms and conditions at: [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

Application advice:

For more detailed application information and graphics please see product datasheet and user instruction.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

